

Bulkhead | 3-CCT | IK10 | IP65

ARTICLE NUMBER: 137-020

View this
product in
our
webshop



14.09.2026 - Disclaimer: information subject to change.



Robust LED wall and ceiling luminaire with IP65 and IK10 ratings. Power output and light colour can be adjusted via integrated DIP switches. Suitable for both indoor and outdoor applications in demanding environments.

Key product features:

- **Colour temperature (K):** 3000 – 5700
- **Impact strength:** IK10
- **Nominal voltage (V):** 34
- **Max. system power (W):** 6
- **Degree of protection (IP), front side:** IP65

Technical specifications:

Product Name	Bulkhead 3-CCT IK10 IP65
Ean	8714984952102
Outer box qty	1st
Lamp type	LED exchangeable
Housing material	Plastic
Housing colour	White
Material cover	Plastic, opal
Suitable for emergency lighting	No
Nominal current	12 - 27mA
Voltage type	AC
Type of control gear	LED operating device current-controlled
With control gear	Yes
Constant light output (CLO)	No
Type of grid	None
Nominal voltage	220 - 240V



14.09.2026 - Disclaimer: information subject to change.

Length	358mm
Width	120mm
Height/depth	82mm
Colour of light	White
Colour rendering index CRI	80-89
Exchangeable control gear	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming phase cut-off (trailing edge)	No
With movement sensor	No
With presence detector	No
Impact strength	IK10
With light sensor	No
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Light distribution	Symmetric
Beam angle	Open beam/diffuse
Light outlet	Direct
Dimming RF	No
Dimming Zigbee	No
Light distributor	Diffuser lens/optic/panel
Surface protection housing	Untreated
Colour consistency (McAdam ellipse)	SDCM3
Rated lifetime L70/B50 at 25 °C	200000h
Colour of light adjustable	Positions
Luminous flux adjustable	Positions

14.09.2026 - Disclaimer: information subject to change.

Max. system power	6W
Beam angle adjustable	No
Power factor	0.9
Type of wiring	Suitable for loop-through wiring
Number of poles	2
Compatible with Casambi	No
Luminaire efficacy	76 - 90lm/W
Dimmable	No
Rated luminous flux according to IEC 62722-2- 1	165 - 505lm
Emergency power supply system	None
Suitable for ceiling mounting	Yes
Connectable conductor cross section	0.5 - 2.5mm??
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Movement sensor/presence detector technology	High frequency
Suitable for workplace according to EN 12464-1	Yes
Unified Glare Ratio (UGR)	17
Degree of protection (IP), rear side	IP65
Degree of protection (IP), front side	IP65
With mounting material	Yes
Colour temperature	3000 - 4000 - 5700K
With connection cord and plug	No
Warranty	5 years
Ambient temperature	-20 - 45??C

14.09.2026 - Disclaimer: information subject to change.



14.09.2026 - Disclaimer: information subject to change.