
TRONIX guided by light

Ceiling light | Ø280mm | 10/15W | 3-CCT | PIR

ARTICLE NUMBER: 136-049

View this product in our webshop



14.11.2026 - Disclaimer: information subject to change.

Robust ceiling light with adjustable light color 3000, 4000 and 5700K, power (10-15W) and motion sensor. Features drop protection, IK08 impact strength and IP54 protection. Ideal for safe, versatile lighting in demanding environments.

Key product features:

- **Colour temperature (K):** 3000 - 5700
- **Housing colour:** White
- **With movement sensor:** Yes
- **Impact strength:** IK08
- **Max. system power (W):** 10 - 15

Technical specifications:


Product Name	Ceiling light | Ø280mm | 10/15W | 3-CCT | PIR
Ean	8714984949799
Outer box qty	10st
Lamp type	LED not exchangeable
Housing material	Aluminium
Housing colour	White
Material cover	Plastic, opal
Suitable for emergency lighting	No
Nominal current	67 - 67mA
Voltage type	AC
Type of control gear	LED operating device current-controlled
With control gear	Yes
Outer diameter	280mm
Constant light output (CLO)	No
Type of grid	Matt
Nominal voltage	220 - 240V

14.11.2026 - Disclaimer: information subject to change.

Height/depth	68mm
Colour of light	White
Colour rendering index CRI	80-89
Exchangeable control gear	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming phase cut-off (trailing edge)	No
With movement sensor	Yes
With presence detector	No
Impact strength	IK08
With light sensor	No
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Dimming RF	No
Dimming Zigbee	No
Light distributor	Other
Surface protection housing	Lacquered
Colour consistency (McAdam ellipse)	SDCM6
Rated lifetime L70/B50 at 25 °C	50000h
Colour of light adjustable	Positions
Luminous flux adjustable	No
Max. system power	15W
Beam angle adjustable	No


14.11.2026 - Disclaimer: information subject to change.


Power factor	0.9
Type of wiring	Ending
Number of poles	3
Compatible with Casambi	No
Luminaire efficacy	100 - 100lm/W
Dimmable	No
Rated luminous flux according to IEC 62722-2- 1	1000 - 1500lm
Emergency power supply system	None
Suitable for ceiling mounting	Yes
Connectable conductor cross section	0.75 - 2.5mm²
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for workplace according to EN 12464-1	No
Degree of protection (IP), front side	IP53
With mounting material	Yes
Colour temperature	3000 - 4000 - 5700K
With connection cord and plug	No
Warranty	5 years
Ambient temperature	-20 - 65°C











14.11.2026 - Disclaimer: information subject to change.