

Ceiling light || Ø300mm | 18W | 3-CCT | dim

ARTICLE NUMBER: 136-040

View this
product in
our
webshop



24.08.2026 - Disclaimer: information subject to change.



Due to the simple adjustment of light color, this ceiling fixture is suitable for placement in various spaces such as offices, living spaces, schools, hotels and other public spaces.

Features

- High quality internal driver with optimum heat regulation
- Can be directly connected by using the terminal block on the fixture
- Adjustable by a CCT switch in the color temperatures 3000K, 4000K and 5700K
- Long service life of 50,000 hours

Technical specifications:

Product Name	Ceiling light Ø300mm 18W 3-CCT dim
Ean	8714984931961
Outer box qty	10st
Lamp type	LED not exchangeable
Housing material	Aluminium
Housing colour	White
Material cover	Plastic, opal
Suitable for emergency lighting	No
Nominal current	75 - 82mA
Voltage type	AC
Type of control gear	LED operating device current-controlled
With control gear	Yes
Outer diameter	300mm
Constant light output (CLO)	No
Type of grid	Matt
Nominal voltage	220 - 240V
Height/depth	58mm



24.08.2026 - Disclaimer: information subject to change.

Colour of light	White
Colour rendering index CRI	80-89
Exchangeable control gear	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming phase cut-off (trailing edge)	Yes
With movement sensor	No
With presence detector	No
Impact strength	IK08
With light sensor	No
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Dimming RF	No
Dimming Zigbee	No
Light distributor	Other
Surface protection housing	Lacquered
Colour consistency (McAdam ellipse)	SDCM6
Rated lifetime L70/B50 at 25 °C	50000h
Colour of light adjustable	Positions
Luminous flux adjustable	Continuously variable
Max. system power	18W
Beam angle adjustable	No
Power factor	0.9

24.08.2026 - Disclaimer: information subject to change.

Type of wiring	Ending
Number of poles	3
Compatible with Casambi	No
Luminaire efficacy	100 - 100lm/W
Dimmable	Yes
Rated luminous flux according to IEC 62722-2- 1	1800 - 1800lm
Emergency power supply system	None
Suitable for ceiling mounting	Yes
Connectable conductor cross section	0.75 - 0.75mm ²
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for workplace according to EN 12464-1	No
Unified Glare Ratio (UGR)	25
Degree of protection (IP), front side	IP53
With mounting material	Yes
Colour temperature	3000 - 4000 - 5700K
With connection cord and plug	No
Warranty	3 years
Ambient temperature	-20 - 65°C

24.08.2026 - Disclaimer: information subject to change.



24.08.2026 - Disclaimer: information subject to change.