Ground spot | 145mm | 10,3W | asymmetrical | 3000K

ARTICLE NUMBER: 140-074

View this product in our webshop



13.11.2026 - Disclaimer: information subject to change.

Subtle yet powerful: these ground spots offer asymmetric optics, warm white light and a durable stainless steel finish for precise façade or object lighting.

Key product features:

- **Light distribution:** Asymmetric
- **Outer diameter (mm)**: 145
- **Built-in diameter (mm):** 129
- **Degree of protection (IP):** IP67
- **Colour temperature (K):** 3000 – 3000
- **Max. system power (W):** 10.3

Technical specifications:

Product Name	Ground spot | 145mm | 10,3W | asymmetrical | 3000K
Ean	8714984935754
Outer box qty	12st
Dimmable	No
Dimming DMX	No
Dimming phase cut-off (trailing edge)	No
Lamp type	LED not exchangeable
Lamp holder	None
Housing colour	Anthracite
Housing material	Aluminium
Material cover	Glass transparent
Connection type	Other
Built-in length	91mm
Built-in height/depth	91mm
Built-in diameter	129mm

13.11.2026 - Disclaimer: information subject to change.

Outer diameter	145mm
Colour of light	White
Colour temperature	3000K
Colour rendering index CRI	80-89
Colour of light adjustable	No
Luminous flux adjustable	No
Constant light output (CLO)	No
Beam angle	41-80° - Wide beam
Beam angle adjustable	No
Voltage type	AC
Nominal voltage	220 - 240V
Nominal current	47 - 47mA
Number of poles	3
Light source included	Yes, fixed LED
Light distributor	Reflector
Light distribution	Asymmetric
Connectable conductor cross section	0.75 - 2.5mm²
Type of control gear	LED operating device current-controlled
With control gear	Yes
Exchangeable control gear	No
Max. surface temperature	50°C
Max. load	100kg
Over rollable	No
Electrical connection with connector system	No
Adjustable	No
Degree of protection (IP)	IP67

13.11.2026 - Disclaimer: information subject to change.

Rated lifetime L70/B50 at 25 °C	50000h
Max. system power	10.3W
Rated luminous flux according to IEC 62722-2- 1	412 - 412lm
Luminaire efficacy	40lm/W
Impact strength	IK09
Power factor	0.93
Type of wiring	Ending
Warranty	2 years
Ambient temperature	-20 - 50°C














13.11.2026 - Disclaimer: information subject to change.