

Ground spot || 24V | 42mm | matt | grey ring |  
2,4W | 3000K

ARTICLE NUMBER: 140-014

View this  
product in  
our  
webshop



04.10.2026 - Disclaimer: information subject to change.

24V ground spot with high-quality stainless steel cover ring and CREE LEDs. Power supply excluded.

## Features

IK08 and IP67

24V, excluding power supply

Extra long connection cable (3 meters)

## Technical specifications:

|                                       |                                                             |
|---------------------------------------|-------------------------------------------------------------|
| Product Name                          | Ground spot    24V   42mm   matt   grey ring   2,4W   3000K |
| Ean                                   | 8714984925960                                               |
| Outer box qty                         | 20st                                                        |
| Dimmable                              | No                                                          |
| Dimming DMX                           | No                                                          |
| Dimming phase cut-off (trailing edge) | No                                                          |
| Lamp type                             | LED not exchangeable                                        |
| Lamp holder                           | None                                                        |
| Housing colour                        | Anthracite                                                  |
| Housing material                      | Aluminium                                                   |
| Material cover                        | Glass matt/satinized                                        |
| Connection type                       | Other                                                       |
| Length                                | 63mm                                                        |
| Height/depth                          | 63mm                                                        |
| Built-in length                       | 90mm                                                        |
| Built-in height/depth                 | 90mm                                                        |
| Built-in diameter                     | 39mm                                                        |
| Outer diameter                        | 42mm                                                        |
| Colour of light                       | White                                                       |
| Colour rendering index CRI            | 80-89                                                       |

04.10.2026 - Disclaimer: information subject to change.


|                                                 |                                         |
|-------------------------------------------------|-----------------------------------------|
| Colour of light adjustable                      | No                                      |
| Luminous flux adjustable                        | No                                      |
| Constant light output (CLO)                     | No                                      |
| Beam angle                                      | > 80° - Extreme wide beam               |
| Beam angle adjustable                           | No                                      |
| Voltage type                                    | DC                                      |
| Nominal voltage                                 | 24 - 24V                                |
| Nominal current                                 | 700 - 700mA                             |
| Number of poles                                 | 2                                       |
| Light distributor                               | Diffuser lens/optic/panel               |
| Light distribution                              | Symmetric                               |
| Connectable conductor cross section             | 0.75 - 2.5mm²                           |
| Type of control gear                            | LED operating device voltage-controlled |
| With control gear                               | No                                      |
| Exchangeable control gear                       | Yes                                     |
| Max. surface temperature                        | 50°C                                    |
| Max. load                                       | 0.25kg                                  |
| Over rollable                                   | No                                      |
| Housing material quality                        | Other                                   |
| Electrical connection with connector system     | No                                      |
| Adjustable                                      | No                                      |
| Degree of protection (IP)                       | IP67                                    |
| Rated lifetime L70/B50 at 25 °C                 | 30000h                                  |
| Max. system power                               | 2.4W                                    |
| Rated luminous flux according to IEC 62722-2- 1 | 111 - 111lm                             |
| Luminaire efficacy                              | 46.3lm/W                                |

04.10.2026 - Disclaimer: information subject to change.



|                     |            |
|---------------------|------------|
| Impact strength     | IK08       |
| Type of wiring      | Ending     |
| Warranty            | 3 years    |
| Ambient temperature | -20 - 50°C |

04.10.2026 - Disclaimer: information subject to change.



  $\varnothing$  40mm(Cut out)

04.10.2026 - Disclaimer: information subject to change.



CARE



SHARE



CONNECT