TRONIX guided by light

LED driver | 150/200/250/300/360mA | max 40V/15W GST18i3

ARTICLE NUMBER: 215-168

View this product in our webshop



12.11.2026 - Disclaimer: information subject to change.

CARE SHARE CONNECT

tronixlighting.com

The ideal LED driver when it comes to a good balance between an attractive price and excellent performance. Thanks to the focus on user-friendliness, you not only have a power supply that works with a wide selection of lamps, but also a product that you can rely on for years to come.

Features


- Constant current output
- Freely adjustable power output from 6 to 15 watts
- Very compact size for easy placement
- IP20 protected

Technical specifications:

Product Name	LED driver | 150/200/250/300/360mA | max 40V/15W GST18i3
Ean	8714984951327
Outer box qty	72st
Housing	Plastic housing
Model	Static
Output voltage	30 - 40V
Output current	150 - 360mA
Suitable for outdoor use	No
Suitable for DC-voltage (primary side)	No
Output power	6 - 15W
Degree of protection (IP)	IP20
Length	103mm
Width	39mm
Height	28mm
Power consumption	15W
Input voltage	200 - 240V

12.11.2026 - Disclaimer: information subject to change.

Frequency input voltage	50 - 60Hz
Overload protection	Yes
Overtemperature protection	Yes
Control method	Non-dimmable
Short-circuit protected	Yes
Ambient temperature	-20 - 45??C
Driver lifetime	50000h
DIN-rail mounting	No
Brand	Tronix Lighting
Dimmable	No
Emergency power supply system	None
Control type	Constant current
Warranty	3 years


28mm
103mm
39mm