

LED driver | eldoLED SOLOdrive 361/A | 30W | 0-10V

ARTICLE NUMBER: 215-622

View this
product in
our
webshop



eldoLED



18.08.2026 - Disclaimer: information subject to change.



The SOLOdrive LED drivers from eldoLED feature a programmable output (constant current) and offer the ability to dim down to 0.1%. Also easy to apply in combination with single color, dimmable LED fixtures on a 0-10V basis.

Features

- Can be combined with a variety of LED lighting, including single color lighting on 0-10V
- Output current: 150 - 1400 mA
- Output voltage: 2 - 55 volts


Technical specifications:

Product Name	LED driver eldoLED SOLOdrive 361/A 30W 0-10V
Ean	8714984943711
Outer box qty	50st
Housing	Plastic housing
Model	Static
Output voltage	2 - 55V
Output current	150 - 1400mA
Suitable for outdoor use	No
Suitable for DC-voltage (primary side)	Yes
Output power	30 - 30W
Degree of protection (IP)	IP20
Length	210mm
Width	40mm
Height	33.5mm
Power consumption	30W
Input voltage	120 - 250V
Frequency input voltage	50 - 60Hz

18.08.2026 - Disclaimer: information subject to change.

PWM modulation	No
Overload protection	Yes
Overtemperature protection	Yes
Control method	0/1-10V
Short-circuit protected	Yes
Ambient temperature	-20 - 50??C
Driver lifetime	50000h
DIN-rail mounting	No
Brand	eldoLED
Dimmable	Yes
Emergency power supply system	None
Control type	Constant current
Warranty	5 years

18.08.2026 - Disclaimer: information subject to change.



18.08.2026 - Disclaimer: information subject to change.