TRONIX guided by light

LED exit sign | surface mount | white | AT | incl. pictogram

ARTICLE NUMBER: 600-022

View this product in our webshop



14.11.2026 - Disclaimer: information subject to change.

Compact and versatile emergency lighting fixture with 25 m viewing distance, multiple mounting options and interchangeable pictograms. Equipped with an automatic self-test function for easy and efficient maintenance.

Key product features

- **Mounting method:** Surface-mounted (wall/ceiling)
- **Max. system power (W):** 1
- **Housing colour:** White
- **Type of indicator:** Single-sided/double-sided
- **Recognition distance (m):** 25
- **Function:** Escape route indication
- **Emergency function monitoring system:** Automatic self-test

Technical specifications:

Product Name	LED exit sign | surface mount | white | AT | incl. pictogram
Ean	8714984935235
Outer box qty	6st
Housing material	Plastic
Lamp type	LED not exchangeable
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal current	150 - 150mA
Type of control gear	LED operating device current-controlled
Battery technology	Lithium-ion
Mounting method	Ceiling surface mounting
Degree of protection (IP)	IP20
Nominal voltage	220 - 240V


Length	315mm
Width	45mm
Height	223mm
Height/depth	223mm
Colour temperature	5000 - 5000K
Exchangeable control gear	No
Function	Escape route signage
With pictogram	Yes
Suitable for standby switching	Yes
Suitable for continuous circuit	Yes
Impact strength	IK00
RAL-number housing	9016
Connection type	Plug-in connection
Light distributor	Diffuser lens/optic/panel
Rated lifetime L70/B50 at 25 ??C	50000h
Luminous flux in standby mode	80lm
Nominal operation time	3 - 3h
Max. system power	3W
Power factor	0.3
Type of wiring	Ending
Number of poles	2
With heating element for battery	No
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Rated luminous flux according to IEC 62722-2- 1	80 - 80lm
Emergency power supply system	Peripheral (individual battery)
Emergency function monitoring system	Automatic self test


14.11.2026 - Disclaimer: information subject to change.


Luminous flux in emergency mode	80lm
Recognition distance	25m
Power consumption in emergency mode	1W
Type of indicator	Single/double-sided
Connectable conductor cross section	0.75 - 2.5mm??
Suitable for labelling type	Insert sheet/plate
Warranty	5 years (battery 2 years)
Ambient temperature	1 - 45??C











14.11.2026 - Disclaimer: information subject to change.