LED panel | butterfly | 30*120 | 3-CCT | UGR<19 | TE dim.

ARTICLE NUMBER: 174-276

View this product in our webshop



10.11.2026 - Disclaimer: information subject to change.

Stylish Butterfly panel with high visual comfort, selectable colour temperature and external dimmable driver. Available in 60x60 and 30x120 cm, incl. EU plug and mounting set.

Key product features:

- **Colour temperature (K):** 3000 - 5700
- **Housing:** White
- **Connection type:** Plug
- **Unified Glare Ratio (UGR):** 19

Technical specifications:

Product Name	LED panel | butterfly | 30*120 | 3-CCT | UGR19 | TE dim.
Ean	8714984938700
Outer box qty	5st
Lamp type	LED not exchangeable
Housing material	Aluminium
Housing colour	White
Material cover	Plastic, opal
Suitable for emergency lighting	No
Nominal current	151 - 151mA
Voltage type	AC
Type of control gear	LED operating device current-controlled
With control gear	Yes
Built-in length	1195mm
Built-in width	295mm
Built-in diameter	49mm
Constant light output (CLO)	No
Type of grid	None
Nominal voltage	220 - 240V

10.11.2026 - Disclaimer: information subject to change.

Length	1195mm
Width	295mm
Height/depth	49mm
Colour of light	White
Colour rendering index CRI	80-89
Exchangeable control gear	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming phase cut-off (trailing edge)	Yes
With movement sensor	No
With presence detector	No
Impact strength	IK02
With light sensor	No
Suitable for surface mounting	Yes
Suitable for built-in mounting	Yes
Light distribution	Symmetric
Beam angle	> 80?? - Extreme wide beam
Light outlet	Direct
Dimming RF	No
Dimming Zigbee	No
Light distributor	Diffuser lens/optic/panel
Surface protection housing	Powder coating
Colour consistency (McAdam ellipse)	SDCM3
Rated lifetime L70/B50 at 25 ??C	60000h
Colour of light adjustable	Positions
Luminous flux adjustable	Continuously variable

10.11.2026 - Disclaimer: information subject to change.

Max. system power	36W
Beam angle adjustable	No
Power factor	0.97
Type of wiring	Ending
Number of poles	2
Built-in height/depth	49mm
Compatible with Casambi	No
Luminaire efficacy	100 - 100lm/W
Dimmable	Yes
Rated luminous flux according to IEC 62722-2- 1	3600 - 3600lm
Emergency power supply system	None
Suitable for ceiling mounting	Yes
Connectable conductor cross section	0.75 - 2.5mm??
Suitable for wall mounting	Yes
Suitable for suspended mounting	Yes
Suitable for workplace according to EN 12464-1	Yes
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP20
With mounting material	Yes
Size	30x120 cm
Colour temperature	3000 - 4000 - 5700K
With connection cord and plug	Yes
Length of power cord	2000mm
Connection type	EU plug
Dimming method	Trailing edge dimming
Warranty	5 years

10.11.2026 - Disclaimer: information subject to change.


Ambient temperature	-20 - 40??C
Connection cable length	2000m











10.11.2026 - Disclaimer: information subject to change.