


LED panel | reflector | 60*60 | 3-CCT | white |
no driver

ARTICLE NUMBER: 173-060

View this
product in
our
webshop



24.08.2026 - Disclaimer: information subject to change.

Efficient LED panel with integrated reflector and low glare value (UGR<17). Supplied without driver, Tunable White compatible. Ideal for applications where visual comfort is key.

Key product features:

- **With control gear:** No
- **Colour temperature (K):** 3000 - 5700
- **Housing colour:** White
- **Light distributor:** Reflector
- **Unified Glare Ratio (UGR):** 17
- **Luminaire efficacy (lm/W):** 130 - 141

This panel is delivered excl. driver, so it can be made dimmable. To make it dimmable, you need the following:

Single color:

- Connector set 173-096;
- Triac, Dali, 1-10V or RF dimmable driver (find related products, set to 650mA);
- Europlug or GST-plug.

Tuneable white:

- Connector set 173-095;
- Dali or RF dimmable driver that is suitable for tuneable white (find related products, set to 650mA);
- Europlug or GST-plug.

Technical specifications:

24.08.2026 - Disclaimer: information subject to change.

Product Name	LED panel reflector 60*60 3-CCT white no driver
Ean	8714984949850
Outer box qty	5st
Lamp type	LED not exchangeable
Housing material	Aluminium
Housing colour	White
Material cover	Other
Suitable for emergency lighting	Yes
Nominal current	700 - 700mA
Voltage type	AC
Type of control gear	LED operating device current-controlled
With control gear	Yes
Built-in length	595mm
Built-in width	595mm
Constant light output (CLO)	No
Type of grid	None
Nominal voltage	38 - 38V
Length	595mm
Width	595mm
Height/depth	12mm
Colour of light	White
Colour rendering index CRI	80-89
Exchangeable control gear	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming phase cut-off (trailing edge)	No

24.08.2026 - Disclaimer: information subject to change.

With movement sensor	No
With presence detector	No
Impact strength	IK02
With light sensor	No
Suitable for surface mounting	Yes
Suitable for built-in mounting	Yes
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Dimming RF	No
Dimming Zigbee	No
Light distributor	Reflector
Surface protection housing	Powder coating
Colour consistency (McAdam ellipse)	SDCM6
Rated lifetime L70/B50 at 25 °C	50000h
Colour of light adjustable	Positions
Luminous flux adjustable	No
Max. system power	26W
Beam angle adjustable	No
Power factor	1
Type of wiring	Ending
Number of poles	2
Built-in height/depth	12mm
Compatible with Casambi	No
Luminaire efficacy	150 - 150lm/W
Dimmable	No

24.08.2026 - Disclaimer: information subject to change.



Rated luminous flux according to IEC
62722-2- 1 3750 - 3750lm

Emergency power supply system None

Emergency function monitoring
system None

Suitable for ceiling mounting Yes

Connectable conductor cross section 0.75 - 0.75mm??

Suitable for wall mounting Yes

Suitable for suspended mounting Yes

Suitable for workplace according to
EN 12464-1 Yes

Unified Glare Ratio (UGR) 17

Degree of protection (IP), rear side IP20

Degree of protection (IP), front side IP20

With mounting material Yes

Size 60x60 cm

Colour temperature 3000 - 4000 - 5700K




With connection cord and plug No

Dimming method Optional

Warranty 5 years

Ambient temperature -20 - 45??C

24.08.2026 - Disclaimer: information subject to change.



24.08.2026 - Disclaimer: information subject to change.