


# LED ropelight | 24V | 30m | vertical | amber

ARTICLE NUMBER: 050-005

View this  
product in  
our  
webshop



24.08.2026 - Disclaimer: information subject to change.



24V LED rope lights from Tronix Lighting are hugely popular due to their versatility and durability, allowing them to be used year-round. Light ropes are ideal for lighting locations both indoors and outdoors. Think of terraces, cafes, swimming pools or as accent lighting at a bar.

## Features

- IP65
- Vertical LED structure
- 36 DIP LEDs per meter
- Clippable per 17 cm rope light
- Including power cable (stripped wire)


## Technical specifications:

|                               |                                              |
|-------------------------------|----------------------------------------------|
| Product Name                  | LED ropelight   24V   30m   vertical   amber |
| Ean                           | 8714984007178                                |
| Outer box qty                 | 1st                                          |
| Model                         | Hose                                         |
| Lamp type                     | LED not exchangeable                         |
| Lamp voltage                  | 0 - 24V                                      |
| Number of nodes per meter     | 36                                           |
| Lamp power per meter          | 1.7W                                         |
| Beam angle                    | 360°                                         |
| Voltage type                  | DC                                           |
| Type of control gear          | LED operating device voltage-controlled      |
| Input voltage tracklights     | 24V                                          |
| With protective cover         | No                                           |
| Length of particular segments | 280mm                                        |
| Degree of protection (IP)     | IP65                                         |
| Self-adhesive                 | No                                           |

24.08.2026 - Disclaimer: information subject to change.

|                                     |                            |
|-------------------------------------|----------------------------|
| Luminous flux per meter             | 100lm                      |
| Total length                        | 30m                        |
| Colour of light                     | Amber                      |
| Suitable for dimmer                 | Yes                        |
| Diameter                            | 13mm                       |
| Exchangeable control gear           | Yes                        |
| Connection type                     | Other                      |
| Rated lifetime L70/B50 at 25 °C     | 20000h                     |
| Colour of light adjustable          | No                         |
| Luminous flux per foot              | 30.48lm                    |
| Luminous flux adjustable            | Continuously variable      |
| Max. system power                   | 51W                        |
| Beam angle adjustable               | No                         |
| Luminaire efficacy                  | 58.8lm/W                   |
| Type of wiring                      | Ending                     |
| Number of poles                     | 2                          |
| Type of power supply                | Mains power supply         |
| Connectable conductor cross section | 0.75 - 0.75mm <sup>2</sup> |
| Colour temperature                  | Amber                      |
| Warranty                            | 2 years                    |
| Ambient temperature                 | -20 - 50°C                 |
| Lowest bending radius               | 100mm                      |
| Connection cable length             | 1.5m                       |

24.08.2026 - Disclaimer: information subject to change.



24.08.2026 - Disclaimer: information subject to change.