

LED spot | downlight | 350mA | 3,3W |
white | 3000K

ARTICLE NUMBER: 148-194

View this
product in
our
webshop



24.08.2026 - Disclaimer: information subject to change.

Compact and Max. system powerful 3.3W LED spot module with reflector. Ideal for focused accent lighting in furniture, interiors and covered outdoor areas. Available in various light colours and housing finishes for a clean, professional look.

Key product features

- **Nominal current (mA):** 0 - 350
- **Max. system power (W):** 3.3
- **Colour temperature (K):** 3000
- **Housing colour:** White
- **Built-in diameter (mm):** 44 – 45

Technical specifications:

Product Name	LED spot downlight 350mA 3,3W white 3000K
Ean	8714984942226
Outer box qty	100st
Lamp type	LED not exchangeable
Lamp holder	None
Housing colour	White
Housing material	Aluminium
Height/depth	40.5mm
Outer diameter	49.28mm
Built-in length	- - -mm
Built-in width	- - -mm
Built-in height	36.8 - -mm
Built-in diameter	43 - 43mm
Suitable for built-in mounting	Yes
Suitable for surface mounting	No
Suitable for pedestal/floor mounting	No



24.08.2026 - Disclaimer: information subject to change.

Suitable for wall mounting	No
Suitable for ceiling mounting	Yes
Suitable for light-track mounting	No
Suitable for clamp-mounting	Yes
With movement sensor	No
With presence detector	No
With light sensor	No
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM3
Colour of light adjustable	No
Colour temperature	3000K
Colour rendering index CRI	90-100
Luminous flux adjustable	Continuously variable
Light outlet	Direct
Beam angle	21-40° - Medium beam
Beam angle adjustable	No
Voltage type	DC
Nominal voltage	9.4 - 9.4V
Nominal current	0 - 350mA
Number of poles	2
Light source included	Yes, fixed LED
Light distributor	Reflector
Light distribution	Symmetric
Connectable conductor cross section	0.3 - 0.3mm ²
Type of control gear	LED operating device current-controlled
With control gear	No
Degree of protection (IP), front side	IP44

24.08.2026 - Disclaimer: information subject to change.

Degree of protection (IP), rear side	IP20
Surface protection	Powder coating
Rated lifetime L70/B50 at 25 °C	50000h
Max. system power	3.3W
Rated luminous flux according to IEC 62722-2- 1	0 - 248lm
Luminaire efficacy	75 - 75lm/W
Power factor	1
Suitable for lamp power	0 - 0W
Surface brushed	No
Type of wiring	Ending
Emergency power supply system	None
Emergency function monitoring system	None
Adjustability	Swivelling
Unified Glare Ratio (UGR)	25
Reflector	High-gloss
Warranty	5 years
Ambient temperature	-20 - 50°C
Control type	Constant current

24.08.2026 - Disclaimer: information subject to change.



24.08.2026 - Disclaimer: information subject to change.