

LED spot | porchlight | 350mA | 3,3W |
alu | 2700K

ARTICLE NUMBER: 148-122

View this
product in
our
webshop



24.08.2026 - Disclaimer: information subject to change.



Compact and stylish 3.3W LED module with reflector, designed for fixed mounting in verandas and soffits – available in different light colours and Housing colours for an elegant and atmospheric finish.

Key product features

- **Nominal current (mA):** 0 - 350
- **Max. system power (W):** 3.3
- **Colour temperature (K):** 2700
- **Housing colour:** Aluminium
- **Built-in diameter (mm):** 33.5 – 37

Technical specifications:

Product Name	LED spot porchlight 350mA 3,3W alu 2700K
Ean	8714984942196
Outer box qty	100st
Lamp type	LED not exchangeable
Lamp holder	None
Housing colour	Aluminium
Housing material	Aluminium
Height/depth	31mm
Outer diameter	42mm
Built-in length	- - -mm
Built-in width	- - -mm
Built-in height	31 - -mm
Built-in diameter	33.6 - 33.6mm
Suitable for built-in mounting	Yes
Suitable for surface mounting	No
Suitable for pedestal/floor mounting	No
Suitable for wall mounting	No

24.08.2026 - Disclaimer: information subject to change.


Suitable for ceiling mounting	Yes
Suitable for light-track mounting	No
Suitable for clamp-mounting	Yes
With movement sensor	No
With presence detector	No
With light sensor	No
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM3
Colour of light adjustable	No
Colour temperature	2700K
Colour rendering index CRI	90-100
Luminous flux adjustable	Continuously variable
Light outlet	Direct
Beam angle	21-40° - Medium beam
Beam angle adjustable	No
Voltage type	DC
Nominal voltage	9.4 - 9.4V
Nominal current	0 - 350mA
Number of poles	2
Light source included	Yes, fixed LED
Light distributor	Reflector
Light distribution	Symmetric
Connectable conductor cross section	0.3 - 0.3mm ²
Type of control gear	LED operating device current-controlled
With control gear	No
Degree of protection (IP), front side	IP44
Degree of protection (IP), rear side	IP20

24.08.2026 - Disclaimer: information subject to change.



Surface protection	Anodised
Rated lifetime L70/B50 at 25 °C	50000h
Max. system power	3.3W
Rated luminous flux according to IEC 62722-2- 1	0 - 230lm
Luminaire efficacy	70 - 70lm/W
Power factor	0.9
Suitable for lamp power	0 - 0W
Surface brushed	Yes
Type of wiring	Ending
Emergency power supply system	None
Emergency function monitoring system	None
Adjustability	not adjustable
Unified Glare Ratio (UGR)	24
Reflector	High-gloss
Warranty	5 years
Ambient temperature	-20 - 50°C
Control type	Constant current

24.08.2026 - Disclaimer: information subject to change.



24.08.2026 - Disclaimer: information subject to change.