

LED spot | porchlight | 700mA | 2,5W |  
alu | 3000K

ARTICLE NUMBER: 148-125

View this  
product in  
our  
webshop



24.08.2026 - Disclaimer: information subject to change.



Porch module with compact dimensions (installation from Ø33.5 mm) and constant current up to 700 mA – specifically designed for narrow roof structures in verandas and patio covers.

## Key product features:

- **Nominal current (mA):** 0 - 700
- **Max. system power (W):** 2.5
- **Colour temperature (K):** 3000
- **Housing colour:** Aluminium
- **Built-in diameter (mm):** 33.5 – 37

## Technical specifications:

|                                      |                                                    |
|--------------------------------------|----------------------------------------------------|
| Product Name                         | LED spot   porchlight   700mA   2,5W   alu   3000K |
| Ean                                  | 8714984915770                                      |
| Outer box qty                        | 100st                                              |
| Lamp type                            | LED not exchangeable                               |
| Lamp holder                          | None                                               |
| Housing colour                       | Aluminium                                          |
| Housing material                     | Aluminium                                          |
| Height/depth                         | 31mm                                               |
| Outer diameter                       | 42mm                                               |
| Built-in length                      | - - -mm                                            |
| Built-in width                       | - - -mm                                            |
| Built-in height                      | 30.3 - -mm                                         |
| Built-in diameter                    | 33.5 - 33.5mm                                      |
| Suitable for built-in mounting       | Yes                                                |
| Suitable for surface mounting        | No                                                 |
| Suitable for pedestal/floor mounting | No                                                 |
| Suitable for wall mounting           | No                                                 |

24.08.2026 - Disclaimer: information subject to change.



|                                       |                                         |
|---------------------------------------|-----------------------------------------|
| Suitable for ceiling mounting         | Yes                                     |
| Suitable for light-track mounting     | No                                      |
| Suitable for clamp-mounting           | Yes                                     |
| With movement sensor                  | No                                      |
| With presence detector                | No                                      |
| With light sensor                     | No                                      |
| Colour of light                       | White                                   |
| Colour consistency (McAdam ellipse)   | SDCM3                                   |
| Colour of light adjustable            | No                                      |
| Colour temperature                    | 3000K                                   |
| Colour rendering index CRI            | 90-100                                  |
| Luminous flux adjustable              | Continuously variable                   |
| Light outlet                          | Direct                                  |
| Beam angle                            | 21-40° - Medium beam                    |
| Beam angle adjustable                 | No                                      |
| Voltage type                          | DC                                      |
| Nominal voltage                       | 3.5 - 3.5V                              |
| Nominal current                       | 0 - 700mA                               |
| Number of poles                       | 2                                       |
| Light source included                 | Yes, fixed LED                          |
| Light distributor                     | Focal lens                              |
| Light distribution                    | Symmetric                               |
| Connectable conductor cross section   | 0.3 - 0.3mm <sup>2</sup>                |
| Type of control gear                  | LED operating device current-controlled |
| With control gear                     | No                                      |
| Degree of protection (IP), front side | IP44                                    |
| Degree of protection (IP), rear side  | IP20                                    |

24.08.2026 - Disclaimer: information subject to change.



|                                                 |                  |
|-------------------------------------------------|------------------|
| Surface protection                              | Anodised         |
| Rated lifetime L70/B50 at 25 °C                 | 50000h           |
| Max. system power                               | 2.5W             |
| Rated luminous flux according to IEC 62722-2- 1 | 0 - 175lm        |
| Luminaire efficacy                              | 70 - 70lm/W      |
| Power factor                                    | 0.9              |
| Suitable for lamp power                         | 0 - 0W           |
| Surface brushed                                 | Yes              |
| Type of wiring                                  | Ending           |
| Emergency power supply system                   | None             |
| Emergency function monitoring system            | None             |
| Adjustability                                   | not adjustable   |
| Unified Glare Ratio (UGR)                       | 22               |
| Reflector                                       | None             |
| Warranty                                        | 5 years          |
| Ambient temperature                             | -20 - 50°C       |
| Control type                                    | Constant current |

24.08.2026 - Disclaimer: information subject to change.



24.08.2026 - Disclaimer: information subject to change.