

LED strip || 24V | 120LED/m 5630 | 5m | IP20
| 2700K | CRI>9

ARTICLE NUMBER: 127-090

View this
product in
our
webshop



25.08.2026 - Disclaimer: information subject to change.

24V flexible LED strip (12 LEDs = 100 mm) with a double row of LEDs for extra light output. With 3M adhesive tape on the back for easy installation.

Features

- IP20 for indoor use
- High color rendering index CRI>90
- Constant color temperature MacAdam: <3
- Long lifespan of 54.000 hours (L70)
- Double layer PCB for good heat dissipation



Technical specifications:

Product Name	LED strip 24V 120LED/m 5630 5m IP20 2700K CRI>9
Ean	8714984916388
Model	Strip
Lamp type	LED not exchangeable
Lamp voltage	0 - 24V
Number of nodes per meter	120
Lamp power per meter	28.8W
Beam angle	120°
Voltage type	DC
Type of control gear	LED operating device voltage-controlled
Input voltage tracklights	24V
With protective cover	No
Length of particular segments	8.3mm
Degree of protection (IP)	IP20
Self-adhesive	Yes
Luminous flux per meter	2358lm
Total length	5m
Width	15mm

25.08.2026 - Disclaimer: information subject to change.

Height/depth	2mm
Colour of light	White
Suitable for dimmer	Yes
Colour rendering index CRI	90-100
Exchangeable control gear	Yes
Connection type	Other
Rated lifetime L70/B50 at 25 °C	54000h
Colour of light adjustable	No
Luminous flux per foot	718.72lm
Luminous flux adjustable	Continuously variable
LED type	SMD
Max. system power	144W
Beam angle adjustable	No
Luminaire efficacy	81.9lm/W
Power factor	1
Type of wiring	Loop-through wiring included
Number of poles	2
Type of power supply	Mains power supply
Connectable conductor cross section	0.5 - 2.5mm ²
Colour temperature	2700K
Warranty	3 years
Ambient temperature	-20 - 50°C
Lowest bending radius	50mm

25.08.2026 - Disclaimer: information subject to change.



25.08.2026 - Disclaimer: information subject to change.