LED strip | 24V | 560LED/m 2010 | 5m | IP20 | 2700K | CRI>95

ARTICLE NUMBER: 127-193

View this product in our webshop



23.11.2026 - Disclaimer: information subject to change.

Ultra-dense 24V LED strip with 560 LEDs per meter. Provides a fully uniform light line, even in shallow profiles – ideal for high-end visible applications.

Key product features:

- **Number of nodes per meter:** 560
- **Lamp power per meter (W):** 20
- **Colour temperature (K):** 2700
- **Width (mm):** 10
- **Length of particular sections (mm):** 12.5
- **Degree of protection (IP):** IP20
- **Luminous flux per meter (Lm):** 1850

Technical specifications:

Product Name	LED strip | 24V | 560LED/m 2010 | 5m | IP20 | 2700K | CRI>95
Ean	8714984935891
Outer box qty	25st
Model	Strip
Lamp type	LED not exchangeable
Lamp voltage	0 - 24V
Number of nodes per meter	560
Lamp power per meter	20W
Beam angle	120°
Voltage type	DC
Type of control gear	LED operating device voltage-controlled
Input voltage tracklights	24V
With protective cover	No
Length of particular segments	12.5mm
Degree of protection (IP)	IP20

23.11.2026 - Disclaimer: information subject to change.

Self-adhesive	Yes
Luminous flux per meter	1722lm
Total length	5m
Width	10mm
Height/depth	1.4mm
Colour of light	White
Suitable for dimmer	Yes
Colour rendering index CRI	90-100
Exchangeable control gear	Yes
Connection type	Other
Rated lifetime L70/B50 at 25 °C	54000h
Colour of light adjustable	No
Luminous flux per foot	524.87lm
Luminous flux adjustable	Continuously variable
LED type	SMD
Max. system power	100W
Beam angle adjustable	No
Luminaire efficacy	83lm/W
Power factor	1
Type of wiring	Loop-through wiring included
Number of poles	2
Connectable conductor cross section	0.5 - 2.5mm²
Colour temperature	2700K
Warranty	3 years
Ambient temperature	-20 - 50°C
Lowest bending radius	50mm

23.11.2026 - Disclaimer: information subject to change.











IP20



23.11.2026 - Disclaimer: information subject to change.