TRONIX guided by light

LED strip | COB | 10W/m | 50m | IP20 | 2200K | free cuttable

ARTICLE NUMBER: 127-219

View this product in our webshop



13.11.2026 - Disclaimer: information subject to change.

This COB LED strip provides a continuous light line with no visible diodes. Freely cuttable for ultimate flexibility. Available in Colour temperatures from 2200K to 6500K, IP20 or IP65, and lengths of 5 or 50 meters.

Key product features:

- **Beam angle (°):** 180
- **Lamp power per meter (W):** 10
- **Colour temperature (K):** 2200
- **Degree of protection (IP):** IP20
- **Luminous flux per meter (lm):** 920
- **Total length (m):** 50

Technical specifications:

Product Name	LED strip | COB | 10W/m | 50m | IP20 | 2200K | free cuttable
Ean	8714984949348
Outer box qty	1st
Model	Strip
Lamp type	LED not exchangeable
Lamp voltage	0 - 24V
Number of nodes per meter	480
Lamp power per meter	10W
Beam angle	180°
Voltage type	DC
Type of control gear	LED operating device voltage-controlled
Input voltage tracklights	24V
With protective cover	No
Degree of protection (IP)	IP20
Self-adhesive	Yes
Luminous flux per meter	630lm


13.11.2026 - Disclaimer: information subject to change.

Total length	50m
Width	8mm
Height/depth	2mm
Colour of light	White
Suitable for dimmer	Yes
Colour rendering index CRI	90-100
Exchangeable control gear	Yes
Connection type	Other
Rated lifetime L70/B50 at 25 °C	54000h
Colour of light adjustable	No
Luminous flux per foot	280.42lm
Luminous flux adjustable	Continuously variable
LED type	COB
Max. system power	500W
Beam angle adjustable	No
Luminaire efficacy	90lm/W
Power factor	1
Type of wiring	Loop-through wiring included
Number of poles	2
Connectable conductor cross section	0.5 - 2.5mm²
Colour temperature	2200K
Warranty	3 years
Ambient temperature	-20 - 50°C
Lowest bending radius	10mm
Connection cable length	0.3m

13.11.2026 - Disclaimer: information subject to change.







13.11.2026 - Disclaimer: information subject to change.