

LED strip | COB 588LED/m | 15W/m | IP20 |
DTW 1800~3000K

ARTICLE NUMBER: 127-139

View this
product in
our
webshop



24.08.2026 - Disclaimer: information subject to change.



COB Dim-to-Warm LED strip with continuous light line and smooth transition from 3000K to 1800K. PWM dimming (<2000 Hz) required for correct functionality and stable colour control.

Key product features

- **Beam angle (°):** 180
- **Lamp power per meter (W):** 15
- **Colour temperature (K):** 1800 - 3000
- **Width (mm):** 12
- **Length of particular sections (mm):** 72.57
- **Degree of protection (IP):** IP20
- **Luminous flux per meter (lm):** 1005

Technical specifications:

Product Name	LED strip COB 588LED/m 15W/m IP20 DTW 1800~3000K
Ean	8714984950870
Outer box qty	25st
Model	Strip
Lamp type	LED not exchangeable
Lamp voltage	0 - 24V
Number of nodes per meter	588
Lamp power per meter	15W
Beam angle	120°
Voltage type	DC
Type of control gear	LED operating device voltage-controlled
Input voltage tracklights	24V
With protective cover	No
Length of particular segments	72.57mm
Degree of protection (IP)	IP20

24.08.2026 - Disclaimer: information subject to change.



Self-adhesive	Yes
Luminous flux per meter	1330lm
Total length	5m
Width	12mm
Height/depth	1.5mm
Colour of light	Multi-coloured
Suitable for dimmer	Yes
Colour rendering index CRI	90-100
Exchangeable control gear	Yes
Connection type	Other
Rated lifetime L70/B50 at 25 °C	54000h
Colour of light adjustable	Continuously variable
Luminous flux per foot	405.38lm
Luminous flux adjustable	Continuously variable
LED type	COB
Max. system power	75W
Beam angle adjustable	No
Luminaire efficacy	83lm/W
Power factor	1
Type of wiring	Loop-through wiring included
Number of poles	2
Connectable conductor cross section	0.5 - 2.5mm ²
Colour temperature	Dim To Warm
Warranty	3 years
Ambient temperature	-20 - 50°C
Lowest bending radius	50mm

24.08.2026 - Disclaimer: information subject to change.



24.08.2026 - Disclaimer: information subject to change.