

Spot | Ø82mm | round | white | 5W |
RGBTW | Zigbee

ARTICLE NUMBER: 136-810

View this
product in
our
webshop



24.08.2026 - Disclaimer: information subject to change.



CARE



SHARE



CONNECT



This round recessed Ø82 mm spotlight combines a clean white design with RGBTW lighting technology. With 5 W output and Zigbee control, it offers full control over colour, Tuneable White and light intensity for flexible lighting applications.

Product features

- **Nominal voltage (V):** 220–240
- **Max. system power (W):** 5
- **Dimming Zigbee:** Yes
- **Height/depth (mm):** 26
- **Built-in diameter (mm):** 68–75
- **Colour temperature:** RGBTW

Technical specifications:

Product Name	Spot Ø82mm round white 5W RGBTW Zigbee
Ean	8714984951914
Outer box qty	100st
Lamp type	LED not exchangeable
Lamp holder	None
Housing colour	White
Housing material	Aluminium
Material cover	Glass transparent
Connection type	GST18i3
Height/depth	26mm
Outer diameter	82mm
Built-in length	- - -mm
Built-in width	- - -mm
Built-in height	26 - -mm




24.08.2026 - Disclaimer: information subject to change.

Built-in diameter	68 - 75mm
Suitable for built-in mounting	Yes
Suitable for surface mounting	No
Suitable for pedestal/floor mounting	No
Suitable for wall mounting	No
Suitable for ceiling mounting	Yes
Suitable for light-track mounting	No
Suitable for clamp-mounting	Yes
With movement sensor	No
With presence detector	No
With light sensor	No
Colour of light	RGBW
Colour consistency (McAdam ellipse)	SDCM3
Colour of light adjustable	Continuously variable
Reflector colour	Silver
Colour temperature	RGBTW
Colour rendering index CRI	90-100
Luminous flux adjustable	Continuously variable
Light outlet	Direct
Beam angle	41-80° - Wide beam
Beam angle adjustable	No
Voltage type	AC
Nominal voltage	220 - 240V
Nominal current	22 - 22mA
Number of poles	2
Light distributor	Reflector
Light distribution	Symmetric

24.08.2026 - Disclaimer: information subject to change.

Connectable conductor cross section	0.5 - 2.5mm ²
Type of control gear	LED operating device current-controlled
Exchangeable control gear	Yes
With control gear	Yes
Degree of protection (IP), front side	IP54
Degree of protection (IP), rear side	IP20
Surface protection	Powder coating
Impact strength	IK02
Rated lifetime L70/B50 at 25 °C	50000h
Max. system power	5W
Rated luminous flux according to IEC 62722-2- 1	300 - 300lm
Luminaire efficacy	60 - 60lm/W
Power factor	0.92
Suitable for lamp power	0 - 0W
Surface brushed	No
Type of wiring	Suitable for loop-through wiring
Emergency power supply system	None
Emergency function monitoring system	None
Adjustability	Rotatable
Unified Glare Ratio (UGR)	24
Reflector	High-gloss
Warranty	5 years
Ambient temperature	-20 - 45°C
Control type	Constant voltage

24.08.2026 - Disclaimer: information subject to change.



24.08.2026 - Disclaimer: information subject to change.