Trailing edge driver for ceiling light bar || GST18/3 con.

ARTICLE NUMBER: 179-061

View this product in our webshop



14.11.2026 - Disclaimer: information subject to change.

The Tronix 'Ceiling light bar' is especially developed for the HeartFelt® Modular and Acoustic Ceiling system: an advanced system for architects, installers and building owners that delivers the right acoustics in every single room, setting or environment.

This sophisticated 'light bar' can easily be attached to any existing HeartFelt® ceiling carrier system with mounting brackets to hold them in place. They can be applied in one single line, in a more playful way, or just in the most efficient way possible.

How it works

1. Choose the fixture
2. Use a mounting bracket for the existing HeartFelt® ceiling: 40HL55, 40HL80 or 40HL105.
3. Connect multiple fixtures to create a single in-line effect (combine with coupler 179-050)
4. Choose one trailing edge or DALI dimmable driver for each luminaire. Every driver inclused a metal mounting plate for fixture attachment.

Technical specifications:

Product Name	Trailing edge driver for ceiling light bar || GST18/3 con.
Ean	8714984937741
Outer box qty	1st
Housing	Plastic housing
Model	Dynamic
Output voltage	220 - 240V
Output current	800 - 800mA
Suitable for outdoor use	No
Suitable for DC-voltage (primary side)	No
Output power	36 - 36W
Degree of protection (IP)	IP20

14.11.2026 - Disclaimer: information subject to change.

Length	160mm
Width	35mm
Height	67mm
Power consumption	36W
Input voltage	- - -V
Frequency input voltage	- - -Hz
Overload protection	Yes
Overtemperature protection	Yes
Control method	Trailing edge dimming
Short-circuit protected	Yes
Ambient temperature	- - -??C
DIN-rail mounting	No
Brand	Tronix Lighting
Dimmable	Yes
Emergency power supply system	None
Control type	Constant voltage
Warranty	2 years

14.11.2026 - Disclaimer: information subject to change.