

Wall lamp | black | 5,7W | 2700K | IP65 | dim

ARTICLE NUMBER: 149-170

View this
product in
our
webshop



14.07.2026 - Disclaimer: information subject to change.



CARE



SHARE



CONNECT

This 143 mm high wall light has a Pyramid-like shape and is suitable for both indoor and outdoor use. The beam (38°) shines downward and is ideal for illuminating a wall, wall or garden fence.

Features

- IP65
- 143 mm high
- 640 Lm
- Incl. internal driver, trailing edge dimmable

Technical specifications:

Product Name	Wall lamp black 5,7W 2700K IP65 dim
Ean	8714984941113
Outer box qty	20st
Lamp type	LED not exchangeable
Housing material	Aluminium
Housing colour	Black
Material cover	Other
Suitable for emergency lighting	No
Nominal current	29 - 29mA
Voltage type	AC
Type of control gear	LED operating device current-controlled
With control gear	Yes
Constant light output (CLO)	No
Type of grid	None
Nominal voltage	220 - 240V
Length	90mm
Width	90mm
Height/depth	143mm

14.07.2026 - Disclaimer: information subject to change.



Colour of light	White
Colour rendering index CRI	80-89
Exchangeable control gear	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming phase cut-off (trailing edge)	Yes
With movement sensor	No
With presence detector	No
Impact strength	IK06
With light sensor	No
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Light distribution	Symmetric/asymmetric
Beam angle	21-40?? - Medium beam
Light outlet	Direct
Dimming RF	No
Dimming Zigbee	No
Light distributor	Other
Surface protection housing	Powder coating
Colour consistency (McAdam ellipse)	SDCM3
Rated lifetime L70/B50 at 25 ??C	50000h
Colour of light adjustable	No
Luminous flux adjustable	Continuously variable
Max. system power	5.8W
Beam angle adjustable	No
Power factor	0.95

14.07.2026 - Disclaimer: information subject to change.



Type of wiring	Ending
Number of poles	3
Compatible with Casambi	No
Luminaire efficacy	75 - 75lm/W
Dimmable	Yes
Rated luminous flux according to IEC 62722-2- 1	428 - 428lm
Emergency power supply system	None
Suitable for ceiling mounting	No
Connectable conductor cross section	0.75 - 0.75mm??
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for workplace according to EN 12464-1	No
Unified Glare Ratio (UGR)	17.9
Degree of protection (IP), front side	IP65
With mounting material	Yes
Colour temperature	2700K
With connection cord and plug	No
Warranty	5 years

14.07.2026 - Disclaimer: information subject to change.



14.07.2026 - Disclaimer: information subject to change.