
TRONIX guided by light

Wall light || Ø160mm | 6W | IP65 | 2700-3000K

ARTICLE NUMBER: 136-255

View this product in our webshop



15.11.2026 - Disclaimer: information subject to change.

This IK08 wall mounted luminaire with UV resistant and corrosion resistant material is suitable for various (industrial) applications. For example, lighting of tunnels, parking garages or walkways. In addition, the fixture is also adjustable in two light colors (2700K-3000K).

Features

- ADC12 aluminum housing with good heat dissipation
- PC 94-V0 anti-UV plastic housing
- 94-V2 corrosion resistant diffuser
- IP65 waterproof
- CCT-2 switch: adjustable in 2700K and 3000K by means of a dip-switch in the fixture
- Available in two sizes

Technical specifications:


Product Name	Wall light || Ø160mm | 6W | IP65 | 2700-3000K
Ean	8714984942486
Outer box qty	12st
Lamp type	LED not exchangeable
Housing material	Aluminium
Housing colour	Black
Material cover	Plastic, opal
Suitable for emergency lighting	No
Nominal current	30 - 30mA
Voltage type	AC
Type of control gear	LED operating device current-controlled
With control gear	Yes
Outer diameter	160mm
Constant light output (CLO)	No
Type of grid	Matt


15.11.2026 - Disclaimer: information subject to change.

Nominal voltage	220 - 240V
Height/depth	93.5mm
Colour of light	White
Colour rendering index CRI	80-89
Exchangeable control gear	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming phase cut-off (trailing edge)	No
With movement sensor	No
With presence detector	No
Impact strength	IK06
With light sensor	No
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Dimming RF	No
Dimming Zigbee	No
Light distributor	Other
Surface protection housing	Lacquered
Colour consistency (McAdam ellipse)	SDCM6
Rated lifetime L70/B50 at 25 °C	50000h
Colour of light adjustable	Positions
Luminous flux adjustable	No
Max. system power	6W

15.11.2026 - Disclaimer: information subject to change.


Beam angle adjustable	No
Power factor	0.9
Type of wiring	Ending
Number of poles	3
Compatible with Casambi	No
Luminaire efficacy	65 - 65lm/W
Dimmable	No
Rated luminous flux according to IEC 62722-2- 1	400 - 400lm
Emergency power supply system	None
Suitable for ceiling mounting	No
Connectable conductor cross section	0.75 - 0.75mm²
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for workplace according to EN 12464-1	No
Degree of protection (IP), front side	IP65
With mounting material	Yes
Colour temperature	2700 - 3000K
With connection cord and plug	No
Warranty	5 years
Ambient temperature	-20 - 65°C














15.11.2026 - Disclaimer: information subject to change.