

Floodlight pro || 50W | 120° | warm white 3000K

Article number: 146-320



The Floodlight for professional use is ideal for 'heavy' applications. Think of areas where lighting is often exposed to external weather conditions. Although this luminaire has a favorable IP rating of IP66, it is also equipped with an external air pressure valve. As a result, air pressure inside and outside the luminaire always remains the same and moisture inside the luminaire has no chance. Because there are different lens options available with a smaller beam angle, these Floodlights are also suitable for:

- Illuminating large buildings such as churches or historic buildings.
- The available asymmetrical lens is suitable for illuminating tennis courts or other sports fields.

Features

- 3x1.0 H05RN-F power cable with schuko plug. Very flexible and strong rubber cable
- Connection gland for possibly changing (a longer) power cable
- The surge protection protects the luminaire against peak voltages
- High light efficiency of >125 Lm / W
- Optional other lenses available (see related products)
- 5 year warranty and 50.000 burning hours

Specifications

Input voltage	220-240V	CRI value	>70	Cable length	150 cm
Power	50 Watt	IP rate	IP66	Connection type	Schuko
Luminous flux	6250 Lm	Sensor	No	Housing material	Aluminium
Color temperature	3000K	Width	190 mm	Housing color	Black (powder paint)
Light color	Warm white	Height	200 mm	Lifetime	50.000 hours
LED type	SMD3030	Height	267 mm (incl. handle)	Certification mark	CE, RoHS
Dimmable	No	Depth	55 mm	Warranty	5 years
Beam angle	120°	Working temperature	-30°C - +50°C		

