

136-500 260mA 4000K specific configuration
Downlight | Ø108mm | white | 5-CCT | 260mA | no driver

Introduction

Purpose of this Document

This document provides information for 136-500 260mA 4000K. During measurement, the product is used in a different mode where output power, colour temperature and/or beam angle are changed from factory standard. These adjustments can be made without altering the product and are designed to be set by the installer. In most cases, the options are set through switches on the product.

Results

Total input power	8.8 W
Correlated Colour Temperature	3871 K
Total lumen output	1020 lm
Efficiency	116 lm/W


Electrical measurement details

Input Power

RMS Input voltage feed. V_{RMS}	34.0 V
RMS Input current feed. I_{RMS}	0.260 A
Total input power	8.8 W
Frequency of input power	0 Hz
Power factor	1.0
Displacement power factor	0.43
Total harmonic distortion of the current	0%
Total harmonic distortion of the voltage	0%


Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 37.5%




Lumen efficiency: 116 lm/W



Harmonics

3rd Harmonic	n/a
5th Harmonic	n/a
7th Harmonic	n/a
9th Harmonic	n/a
11th Harmonic	n/a

Current Harmonics %




136-500 260mA 4000K specific configuration

Colour measurement details


Total lumen output 1020 lm
 Correlated Colour Temperature 3871 K
 Colour coordinates CIE 1931 (x;y) = (0.382;0.366)
 Colour deviation from BBL Duv = -0.0057

TM30-18 Colour Fidelity Index R_f 93.2
 TM30-18 Colour Gamut Index R_g 103.8
 Colour Rendering Index (Ra) CRI 95.9
 Colour Rendering Index. (red component) $R_9 = 94.3$


Colour Quality Scale CQS = 95.5
 Television Lighting Consistency Index TLCI = 91



Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	95	-1%	0%
C2	97	1%	0%
C3	94	1%	3%
C4	96	0%	1%
C5	93	0%	2%
C6	93	4%	2%
C7	95	3%	1%
C8	94	2%	1%
C9	95	2%	2%
C10	96	0%	2%
C11	89	4%	6%
C12	89	5%	1%
C13	92	3%	-5%
C14	90	8%	-4%
C15	91	2%	-4%
C16	89	2%	-6%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale