



PHOTOMETRIC LIGHT REPORT

Downlight | Ø140mm | white | 5-CCT | 6~15W | EU plug

Article number: 136-511



Go to the
webshop
of Tronix
Lighting



TRONIX



136-511 Downlight | Ø140mm | white | 5-CCT | 6~15W | EU plug

Introduction

Purpose of this Document

This document provides accurate and objective photometric data for Tronix Lighting item 136-511. All information is based on actual measurements taken from standard production units. No modifications were made to enhance performance results. In some cases, minor adjustments—such as temporary removal of covers, cables, or mounting features—were necessary for testing purposes. These did not influence product performance.

Test Methodology

Testing was conducted using randomly selected, unopened samples from regular inventory. All tests comply with the LM-79-19 standard, the recognized method for photometric and electrical measurements of LED and OLED luminaires. This standard, an update of IES LM-79-2008, outlines environmental test conditions, stabilization procedures, measurement methods, and approved instruments. It uses absolute photometry, meaning results directly reflect the performance of the tested product, without comparison to rated lamp standards.

Product 136-511 was tested using:

- A photogoniometer to measure luminous intensity distribution at various angles
- An integrating sphere to determine total luminous flux and colour characteristics

Compliance & Certification

Item 136-511 meets the requirements of the following EU directives. Tronix Lighting certifies that all relevant tests were executed in accordance with the applicable standards, and the CE mark is applied accordingly:

- General Product Safety – Directive 2023/988/EC
- Low Voltage Directive (LVD) – Directive 2014/35/EU
- Electromagnetic Compatibility (EMC) – Directive 2004/108/EC
- Ecodesign – Directive 2009/125/EC
- RoHS 3 – Directive 2011/65/EU + Amendment 2015/863/EU

Recycling & Sustainability

Tronix Lighting is affiliated with national recycling systems for electrical and electronic waste. The luminaire is over 90% recyclable when disposed of as electronic waste at end of life. In addition, Tronix Lighting participates in national packaging recycling schemes, ensuring full compliance with both the WEEE and packaging directives.

136-511 Downlight | Ø140mm | white | 5-CCT | 6~15W | EU plug

Laboratory and equipment

Laboratory owner and location	Tronix Lighting BV. Uden. The Netherlands
Gonio spectrometer system and type	Viso Systems Type C. horizontal
Spectrometer manufacturer and model	(Gonio) Ocean Optics STS VIS (Sphere) Admesy HERA VIS 380–780nm
Flicker meter manufacturer and model	Viso Systems LabFlicker
Oscilloscope manufacturer and model	Tektronix MDO3024 oscilloscope (4 Channels. 200 MHz)
Power meter manufacturer and model	Vitretek PA900 Precision Multi-Channel Harmonic Power Analyzer
Power source manufacturer and model	(DC) Keithley Source Measure Unit SMU-2420 3A DC Source Meter (AC) Chroma 61601 AC Source
Datalogger Manufacturer and Model	Omega 8-Channel Thermocouple Thermometer/Data Logger

Measurement conditions gonio spectrometer

Number of C-planes and Resolution	2 planes – 180°
γ (gamma)-Resolution	2°
Test Distance	1.14 m
Room Temperature and Humidity	22°C +/- 10% – RH 50% +/- 20%
Input Power. Power and Displacement Factors	13.9 W – PF 0.96 – DPF 0.97
Frequency of Input Power	50 Hz
Warm-up Time and Variation	Lamp stabilized in 15 min 0 sec --0.1%

Tested light source

Manufacturer and Order Code	Tronix Lighting – 136-511
Product Description	Downlight Ø140mm white 5-CCT 6~15W EU plug

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	1416 lm – 0% / 100%
Efficiency	102 lm/W
Energy efficiency class	F
Peak Intensity and Beam Angle	1449 cd – 57.8°
Correlated Colour Temperature	CCT = 3577 K
Colour Shift. CIE duv	Duv -0.0052
Colour Rendering Index	CRI 95.8
Colour Rendering TM30-18	R _f 93.3 – R _g 103.3
Television Lighting Consistency Index	TLCI = 90
Flicker	SVM 0 – PstLM 0.04

136-511 Downlight | Ø140mm | white | 5-CCT | 6~15W | EU plug

Electrical measurement details

Input Power


RMS Input voltage feed. V_{RMS} 230 V
 RMS Input current feed. I_{RMS} 0.063 A
 Total input power 13.9 W

Frequency of input power 50 Hz
 Power factor 0.96
 Displacement power factor 0.97

Total harmonic distortion of the current 10.4%
 Total harmonic distortion of the voltage 2.44%

Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 32.7%




Lumen efficiency: 102 lm/W



Harmonics

3rd Harmonic 5.68%
 5th Harmonic 7.6%
 7th Harmonic 1.37%
 9th Harmonic 1.65%
 11th Harmonic 0.91%

Current Harmonics %



Stabilization Details

Warm-up Conditions

Stable period 15 min
 Stable change max 2.0%
 Minimum warm-up time 15 min

Colour temperature change during warm-up

15 min CCT start 3577 K
 2.0% CCT shift 0 K
 15 min CCT end 3577 K

Warm-up Results

Total warmup time Lamp stabilized in 15 min 0 sec
 Warmup variation -0.1%

Output intensity change during warm-up

Output start 1417 lm
 Output change lm
 Output end 1416 lm


136-511 Downlight | Ø140mm | white | 5-CCT | 6~15W | EU plug

Colour measurement details


Total lumen output 1416 lm
 Correlated Colour Temperature 3577 K
 Colour coordinates CIE 1931 (x;y) = (0.396;0.375)
 Colour deviation from BBL Duv = -0.0052

TM30-18 Colour Fidelity Index R_f 93.3
 TM30-18 Colour Gamut Index R_g 103.3
 Colour Rendering Index (Ra) CRI 95.8
 Colour Rendering Index. (red component) $R_9 = 86.2$


Colour Quality Scale CQS = 95.2
 Television Lighting Consistency Index TLCI = 90



Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	95	-2%	0%
C2	96	-1%	1%
C3	93	1%	3%
C4	96	0%	1%
C5	93	1%	2%
C6	93	4%	2%
C7	95	3%	0%
C8	94	3%	0%
C9	96	1%	1%
C10	95	0%	2%
C11	90	3%	5%
C12	88	5%	0%
C13	91	3%	-5%
C14	89	5%	-6%
C15	91	2%	-5%
C16	89	1%	-7%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale

136-511 Downlight | Ø140mm | white | 5-CCT | 6~15W | EU plug

Flicker / temporal light artefacts details

Measurement conditions

Flicker meter type	Viso Systems LabFlicker
Flicker/TLA sample rate	20000 samples/s
Measurement time	5x 180 seconds (15 minutes) for PstLM. 1.2 sec for all other indices

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency	10000 Hz
Percent flicker	1.03 %
Flicker index	0


TLA indices (according IEC TR 61547-1, EN 61000-3-3 and EN 61000-4-15)

An LED luminaire is considered flicker-free if the SVM value is ≤ 0.4 and if the PstLM value is ≤ 1.0


PstLM value ($F < 80$ Hz) 0.04

SVM value ($80 < F < 2000$ Hz) 0


Flicker frame (one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789-2015 Lighting Flicker Risk Zones




Document revision date: 3-9-2025 Measurement serial: VFR-250825-10943-SW

136-511 Downlight | Ø140mm | white | 5-CCT | 6~15W | EU plug

Beam angle

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	1416 lm
Lumen Up/Down	0% / 100%
Peak Intensity	1449 cd
Beam Angle (50%)	57.8°
Beam Angle (90%)	57.8°
Beam Angle (10%)	57.8°

Cut-off Angle

Average 2.5%	105.4°
--------------	--------

Field Angle

Average 10%	91.9°
-------------	-------


Intensity Ratio

In 120° cone	96.8%
In 90° cone	91.6%

C planes

C000-C180
C090-C270


Linear distribution diagram - Intensity (candela) vs γ-angle



Document revision date: 3-9-2025 Measurement serial: VFR-250825-10943-SW

136-511 Downlight | Ø140mm | white | 5-CCT | 6~15W | EU plug

Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
1449	362	161	91	58	40	30	23	18	14	12	10	9	7	6	6	5	4	4	4	lux
134.6	33.6	15	8.4	5.4	3.7	2.7	2.1	1.7	1.3	1.1	0.9	0.8	0.7	0.6	0.5	0.5	0.4	0.4	0.3	fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1449	1447	1440	1424	1401	1370	1329	1284	1235	1182	1123	1054	972	872	770	677	595	524	457	389	cd
100%	100%	99%	98%	97%	95%	92%	89%	85%	82%	78%	73%	67%	60%	53%	47%	41%	36%	32%	27%	of 0°val

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1449	1447	1440	1424	1401	1370	1329	1284	1235	1182	1123	1054	972	872	770	677	595	524	457	389	cd
100%	100%	99%	98%	97%	95%	92%	89%	85%	82%	78%	73%	67%	60%	53%	47%	41%	36%	32%	27%	of 0°val

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1449	1447	1440	1424	1401	1370	1329	1284	1235	1182	1123	1054	972	872	770	677	595	524	457	389	cd
100%	100%	99%	98%	97%	95%	92%	89%	85%	82%	78%	73%	67%	60%	53%	47%	41%	36%	32%	27%	of 0°val

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1449	1447	1440	1424	1401	1370	1329	1284	1235	1182	1123	1054	972	872	770	677	595	524	457	389	cd
100%	100%	99%	98%	97%	95%	92%	89%	85%	82%	78%	73%	67%	60%	53%	47%	41%	36%	32%	27%	of 0°val



136-511 Downlight | Ø140mm | white | 5-CCT | 6~15W | EU plug

Light Planning – UGR table

Uncorrected, comprehensive UGR table according to CIE 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	18.7	19.4	18.8	19.7	19.9	18.7	19.4	18.8	19.7	19.9
	3H	18.7	19.6	19.1	19.8	20.0	18.7	19.6	19.1	19.8	20.0
	4H	18.9	19.7	19.3	19.9	20.2	18.9	19.7	19.3	19.9	20.2
	6H	19.1	19.8	19.4	20.1	20.5	19.1	19.8	19.4	20.1	20.5
	8H	19.2	19.8	19.5	20.2	20.5	19.2	19.8	19.5	20.2	20.5
	12H	19.2	19.8	19.6	20.2	20.6	19.2	19.8	19.6	20.2	20.6
4H	2H	18.5	19.3	18.9	19.5	19.8	18.5	19.3	18.9	19.5	19.8
	3H	18.8	19.5	19.2	19.8	20.3	18.8	19.5	19.2	19.8	20.3
	4H	19.0	19.6	19.5	20.1	20.6	19.0	19.6	19.5	20.1	20.6
	6H	19.3	19.9	19.8	20.3	20.6	19.3	19.9	19.8	20.3	20.6
	8H	19.4	20.0	20.0	20.3	20.7	19.4	20.0	20.0	20.3	20.7
	12H	19.5	20.0	20.0	20.4	20.8	19.5	20.0	20.0	20.4	20.8
8H	4H	19.1	19.7	19.6	20.0	20.4	19.1	19.7	19.6	20.0	20.4
	6H	19.5	19.9	20.0	20.4	20.9	19.5	19.9	20.0	20.4	20.9
	8H	19.8	20.1	20.3	20.6	21.2	19.8	20.1	20.3	20.6	21.2
	12H	19.9	20.2	20.5	20.7	21.3	19.9	20.2	20.5	20.7	21.3
12H	4H	19.1	19.5	19.6	19.9	20.4	19.1	19.5	19.6	19.9	20.4
	6H	19.6	19.9	20.1	20.4	21.0	19.6	19.9	20.1	20.4	21.0
	8H	19.8	20.1	20.4	20.6	21.2	19.8	20.1	20.4	20.6	21.2
Variations with the observer position for the luminaire spacings. S:											
S = 1.0H		2.1 / -2.1					2.1 / -2.1				
S = 1.5H		4.1 / -2.3					4.1 / -2.3				
S = 2.0H		5.9 / -2.5					5.9 / -2.5				

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	106	106	106	102	102	102	100	
1	113	110	107	105	110	108	105	103	103	102	100	100	98	97	96	95	94	92
2	107	101	97	93	104	100	95	92	96	93	90	93	90	88	90	88	86	85
3	101	94	88	84	99	92	87	83	90	85	82	87	84	81	85	82	79	78
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72
5	90	81	75	70	88	80	74	70	78	73	69	76	72	69	75	71	68	66
6	85	76	69	65	84	75	69	64	73	68	64	72	67	64	70	66	63	62
7	81	71	64	60	79	70	64	60	69	63	59	68	63	59	66	62	59	57
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53
9	73	63	56	52	72	62	56	52	61	56	52	60	55	52	59	55	51	50
10	69	59	53	49	68	58	53	49	58	52	49	57	52	48	56	52	48	47