

137-021 6W 5700K specific configuration Bulkhead | 3-CCT | IK10 | IP65

Introduction

Purpose of this Document

This document provides information for 137-021 6W 5700K. During measurement, the product is used in a different mode where output power, colour temperature and/or beam angle are changed from factory standard. These adjustments can be made without altering the product and are designed to be set by the installer. In most cases, the options are set through switches on the product.

Results

Total input power	5.7 W
Correlated Colour Temperature	5868 K
Total lumen output	512 lm
Efficiency	90 lm/W


Electrical measurement details

Input Power

RMS Input voltage feed. V_{RMS}	232 V
RMS Input current feed. I_{RMS}	0.028 A
Total input power	5.7 W
Frequency of input power	50 Hz
Power factor	0.89
Displacement power factor	0.93
Total harmonic distortion of the current	25.81%
Total harmonic distortion of the voltage	2.7%


Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 28.8%




Lumen efficiency: 90 lm/W



Harmonics

3rd Harmonic	15.13%
5th Harmonic	15.3%
7th Harmonic	4.09%
9th Harmonic	8.59%
11th Harmonic	3.25%

Current Harmonics %




137-021 6W 5700K specific configuration

Colour measurement details



Total lumen output 512 lm
 Correlated Colour Temperature 5868 K
 Colour coordinates CIE 1931 (x;y) = (0.325;0.336)
 Colour deviation from BBL Duv = 0.0009

TM30-18 Colour Fidelity Index R_f 82.7
 TM30-18 Colour Gamut Index R_g 94.5
 Colour Rendering Index (Ra) CRI 85.2
 Colour Rendering Index. (red component) R_9 = 21.6


Colour Quality Scale CQS = 81.0
 Television Lighting Consistency Index TLCI = 77



Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	77	-12%	1%
C2	85	-6%	6%
C3	82	-4%	8%
C4	86	-2%	5%
C5	86	-3%	2%
C6	93	-2%	-1%
C7	92	-5%	-1%
C8	84	-9%	4%
C9	80	-9%	15%
C10	71	-4%	18%
C11	73	4%	17%
C12	90	5%	4%
C13	87	8%	-5%
C14	86	3%	-8%
C15	72	6%	-23%
C16	87	-7%	-4%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale