



PHOTOMETRIC LIGHT REPORT

**Spot | Ø51*29mm | 24V |
4W | black | 2700K/3000K
| dim**

Article number: 148-826



Go to the
webshop
of Tronix
Lighting



TRONIX



148-826 Spot | Ø51*29mm | 24V | 4W | black | 2700K/3000K | dim

Introduction

Purpose of this Document

This document provides accurate and objective photometric data for Tronix Lighting item 148-826. All information is based on actual measurements taken from standard production units. No modifications were made to enhance performance results. In some cases, minor adjustments—such as temporary removal of covers, cables, or mounting features—were necessary for testing purposes. These did not influence product performance.

Test Methodology

Testing was conducted using randomly selected, unopened samples from regular inventory. All tests comply with the LM-79-19 standard, the recognized method for photometric and electrical measurements of LED and OLED luminaires. This standard, an update of IES LM-79-2008, outlines environmental test conditions, stabilization procedures, measurement methods, and approved instruments. It uses absolute photometry, meaning results directly reflect the performance of the tested product, without comparison to rated lamp standards.

Product 148-826 was tested using:

- A photogoniometer to measure luminous intensity distribution at various angles
- An integrating sphere to determine total luminous flux and colour characteristics

Compliance & Certification

Item 148-826 meets the requirements of the following EU directives. Tronix Lighting certifies that all relevant tests were executed in accordance with the applicable standards, and the CE mark is applied accordingly:

- General Product Safety – Directive 2023/988/EC
- Low Voltage Directive (LVD) – Directive 2014/35/EU
- Electromagnetic Compatibility (EMC) – Directive 2004/108/EC
- Ecodesign – Directive 2009/125/EC
- RoHS 3 – Directive 2011/65/EU + Amendment 2015/863/EU

Recycling & Sustainability

Tronix Lighting is affiliated with national recycling systems for electrical and electronic waste. The luminaire is over 90% recyclable when disposed of as electronic waste at end of life. In addition, Tronix Lighting participates in national packaging recycling schemes, ensuring full compliance with both the WEEE and packaging directives.

148-826 Spot | Ø51*29mm | 24V | 4W | black | 2700K/3000K | dim

Laboratory and equipment

Laboratory owner and location	Tronix Lighting BV. Uden. The Netherlands
Gonio spectrometer system and type	Viso Systems Type C. horizontal
Spectrometer manufacturer and model	(Gonio) Ocean Optics STS VIS (Sphere) Admesy HERA VIS 380–780nm
Flicker meter manufacturer and model	Viso Systems LabFlicker
Oscilloscope manufacturer and model	Tektronix MDO3024 oscilloscope (4 Channels. 200 MHz)
Power meter manufacturer and model	Vitrek PA900 Precision Multi-Channel Harmonic Power Analyzer
Power source manufacturer and model	(DC) Keithley Source Measure Unit SMU-2420 3A DC Source Meter (AC) Chroma 61601 AC Source
Datalogger Manufacturer and Model	Omega 8-Channel Thermocouple Thermometer/Data Logger

Measurement conditions gonio spectrometer

Number of C-planes and Resolution	2 planes – 180°
γ (gamma)-Resolution	7.5°
Test Distance	0.66 m
Room Temperature and Humidity	22°C +/- 10% – RH 50% +/- 20%
Input Power. Power and Displacement Factors	4.2 W – PF 1.0 – DPF 0.7
Frequency of Input Power	0 Hz
Warm-up Time and Variation	Lamp stabilized in 15 min 3 sec --1.3%

Tested light source

Manufacturer and Order Code	Tronix Lighting – 148-826
Product Description	Spot Ø51*29mm 24V 4W black 2700K/3000K dim

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	203 lm – 0.44% / 99.56%
Efficiency	48 lm/W
Energy efficiency class	G
Peak Intensity and Beam Angle	119 cd – 81.2°
Correlated Colour Temperature	CCT = 2552 K
Colour Shift. CIE duv	Duv -0.0007
Colour Rendering Index	CRI 92.1
Colour Rendering TM30-18	R _f 91.4 – R _g 98.3
Television Lighting Consistency Index	TLCI = 89
Flicker	SVM n/a – PstLM n/a

148-826 Spot | Ø51*29mm | 24V | 4W | black | 2700K/3000K | dim

Electrical measurement details

Input Power


RMS Input voltage feed. V_{RMS} 24.0 V
 RMS Input current feed. I_{RMS} 0.177 A
 Total input power 4.2 W

Frequency of input power 0 Hz
 Power factor 1.0
 Displacement power factor 0.7

Total harmonic distortion of the current 0%
 Total harmonic distortion of the voltage 0%

Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 17.0%




Lumen efficiency: 48 lm/W



Harmonics

3rd Harmonic n/a
 5th Harmonic n/a
 7th Harmonic n/a
 9th Harmonic n/a
 11th Harmonic n/a

Current Harmonics %



Stabilization Details

Warm-up Conditions

Stable period	15 min	CCT start	2554 K
Stable change max	2.0%	CCT shift	-2 K
Minimum warm-up time	15 min	CCT end	2552 K

Colour temperature change during warm-up

Warm-up Results

Total warmup time	Lamp stabilized in 15 min 3 sec	Output start	205 lm
Warmup variation	-1.3%	Output change	-3 lm
		Output end	203 lm

Output intensity change during warm-up


148-826 Spot | Ø51*29mm | 24V | 4W | black | 2700K/3000K | dim

Colour measurement details


Total lumen output 203 lm
 Correlated Colour Temperature 2552 K
 Colour coordinates CIE 1931 (x;y) = (0.471;0.411)
 Colour deviation from BBL Duv = -0.0007

TM30-18 Colour Fidelity Index R_f 91.4
 TM30-18 Colour Gamut Index R_g 98.3
 Colour Rendering Index (Ra) CRI 92.1
 Colour Rendering Index. (red component) R_9 = 52.9


Colour Quality Scale CQS = 89.4
 Television Lighting Consistency Index TLCI = 89



Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	89	-6%	1%
C2	91	-4%	3%
C3	91	-1%	5%
C4	94	-2%	1%
C5	96	-1%	2%
C6	96	1%	1%
C7	95	-2%	-1%
C8	97	-1%	1%
C9	93	-2%	3%
C10	91	-1%	6%
C11	90	4%	6%
C12	90	5%	-1%
C13	89	3%	-8%
C14	86	3%	-11%
C15	90	-3%	-4%
C16	85	-5%	-10%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale

148-826 Spot | Ø51*29mm | 24V | 4W | black | 2700K/3000K | dim

Flicker / temporal light artefacts details

Measurement conditions

Flicker meter type	Viso Systems LabFlicker
Flicker/TLA sample rate	n/a samples/s
Measurement time	5x 180 seconds (15 minutes) for PstLM. 1.2 sec for all other indices

Flicker indices according to Illuminating Engineering Society (IES)


Flicker frequency	n/a Hz
Percent flicker	n/a %
Flicker index	n/a

TLA indices (according IEC TR 61547-1, EN 61000-3-3 and EN 61000-4-15)


An LED luminaire is considered flicker-free if the SVM value is ≤ 0.4 and if the PstLM value is ≤ 1.0

PstLM value ($F < 80$ Hz)	n/a
SVM value ($80 < F < 2000$ Hz)	n/a


Flicker frame (one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)




IEEE 1789-2015 Lighting Flicker Risk Zones



148-826 Spot | Ø51*29mm | 24V | 4W | black | 2700K/3000K | dim

Beam angle

Luminous Intensity diagram



Main Values

Output (total Lumen)	203 lm
Lumen Up/Down	0.44% / 99.56%
Peak Intensity	119 cd
Beam Angle (50%)	81.2°
Beam Angle (90%)	81.2°
Beam Angle (10%)	81.2°

Cut-off Angle

Average 2.5%	149.2°
--------------	--------

Field Angle

Average 10%	122.5°
-------------	--------


Intensity Ratio

In 120° cone	94.2%
In 90° cone	75.8%

C planes


C000-C180
C090-C270

Linear distribution diagram - Intensity (candela) vs γ-angle



148-826 Spot | Ø51*29mm | 24V | 4W | black | 2700K/3000K | dim

Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
119	30	13	7	5	3	2	2	1	1	1	1	1	1	1	0	0	0	0	0	lux
11.1	2.8	1.2	0.7	0.4	0.3	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0	0	0	0	0	0	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
119	119	117	113	106	97	86	74	61	48	35	23	14	7	5	3	1	0	0	0	cd
100%	100%	98%	94%	89%	81%	72%	62%	51%	40%	29%	19%	12%	6%	4%	2%	1%	0%	0%	0%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
119	119	117	113	106	97	86	74	61	48	35	23	14	7	5	3	1	0	0	0	cd
100%	100%	98%	94%	89%	81%	72%	62%	51%	40%	29%	19%	12%	6%	4%	2%	1%	0%	0%	0%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
119	119	117	113	106	97	86	74	61	48	35	23	14	7	5	3	1	0	0	0	cd
100%	100%	98%	94%	89%	81%	72%	62%	51%	40%	29%	19%	12%	6%	4%	2%	1%	0%	0%	0%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
119	119	117	113	106	97	86	74	61	48	35	23	14	7	5	3	1	0	0	0	cd
100%	100%	98%	94%	89%	81%	72%	62%	51%	40%	29%	19%	12%	6%	4%	2%	1%	0%	0%	0%	of 0°val

Document revision date: 31-8-2026 Measurement serial: VFR-260622-13594-SW



148-826 Spot | Ø51*29mm | 24V | 4W | black | 2700K/3000K | dim

Light Planning – UGR table

Uncorrected, comprehensive UGR table according to CIE 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	24.6	25.6	24.8	25.9	26.1	24.6	25.6	24.8	25.9	26.1
	3H	24.5	25.6	24.9	25.8	26.0	24.5	25.6	24.9	25.8	26.0
	4H	24.5	25.5	24.9	25.8	26.0	24.5	25.5	24.9	25.8	26.0
	6H	24.5	25.4	24.8	25.7	26.0	24.5	25.4	24.8	25.7	26.0
	8H	24.5	25.3	24.8	25.6	26.0	24.5	25.3	24.8	25.6	26.0
	12H	24.4	25.2	24.8	25.6	26.0	24.4	25.2	24.8	25.6	26.0
4H	2H	24.5	25.5	24.9	25.8	26.0	24.5	25.5	24.9	25.8	26.0
	3H	24.6	25.4	25.0	25.8	26.2	24.6	25.4	25.0	25.8	26.2
	4H	24.6	25.3	25.0	25.7	26.3	24.6	25.3	25.0	25.7	26.3
	6H	24.5	25.3	25.0	25.6	26.0	24.5	25.3	25.0	25.6	26.0
	8H	24.5	25.2	25.0	25.5	25.9	24.5	25.2	25.0	25.5	25.9
	12H	24.4	25.0	24.9	25.4	25.9	24.4	25.0	24.9	25.4	25.9
8H	4H	24.5	25.2	25.0	25.5	25.9	24.5	25.2	25.0	25.5	25.9
	6H	24.5	25.0	25.0	25.4	26.0	24.5	25.0	25.0	25.4	26.0
	8H	24.4	24.9	25.0	25.4	26.0	24.4	24.9	25.0	25.4	26.0
	12H	24.4	24.8	25.0	25.3	25.9	24.4	24.8	25.0	25.3	25.9
12H	4H	24.4	25.0	24.9	25.4	25.9	24.4	25.0	24.9	25.4	25.9
	6H	24.4	24.9	25.0	25.4	26.0	24.4	24.9	25.0	25.4	26.0
	8H	24.4	24.8	25.0	25.3	25.9	24.4	24.8	25.0	25.3	25.9
Variations with the observer position for the luminaire spacings. S:											
S = 1.0H		0.8 / -1.7					0.8 / -1.7				
S = 1.5H		2.3 / -4.2					2.3 / -4.2				
S = 2.0H		3.9 / -6.6					3.9 / -6.6				

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	106	106	106	102	102	102	100	
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	91	89
2	104	98	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79
3	97	88	82	77	94	87	81	76	84	79	75	81	77	73	79	75	72	70
4	90	80	73	68	88	79	72	67	77	71	66	74	69	65	72	68	64	63
5	84	73	66	60	82	72	65	60	70	64	59	68	63	59	66	62	58	56
6	78	67	59	54	76	66	59	54	64	58	53	63	57	53	61	56	52	51
7	73	62	54	49	72	61	54	49	59	53	48	58	52	48	57	51	48	46
8	69	57	49	44	67	56	49	44	55	48	44	54	48	44	53	47	43	42
9	64	53	45	40	63	52	45	40	51	45	40	50	44	40	49	44	40	38
10	61	49	42	37	60	48	42	37	47	41	37	47	41	37	46	40	37	35