

173-032 6W 3000K specific configuration
LED panel | 30*60 | 6/8/10/13/15W | 3-CCT | EU plug

Introduction

Purpose of this Document

This document provides information for 173-032 6W 3000K. During measurement, the product is used in a different mode where output power, colour temperature and/or beam angle are changed from factory standard. These adjustments can be made without altering the product and are designed to be set by the installer. In most cases, the options are set through switches on the product.

Results

Total input power	6.2 W
Correlated Colour Temperature	3150 K
Total lumen output	836 lm
Efficiency	135 lm/W


Electrical measurement details

Input Power

RMS Input voltage feed. V_{RMS}	232 V
RMS Input current feed. I_{RMS}	0.030 A
Total input power	6.2 W
Frequency of input power	50 Hz
Power factor	0.88
Displacement power factor	0.89
Total harmonic distortion of the current	18.56%
Total harmonic distortion of the voltage	2.61%

Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 38.7%




Lumen efficiency: 135 lm/W



Harmonics

3rd Harmonic	12.51%
5th Harmonic	9.52%
7th Harmonic	0.79%
9th Harmonic	7.43%
11th Harmonic	3.34%

Current Harmonics %




173-032 6W 3000K specific configuration

Colour measurement details


Total lumen output 836 lm
 Correlated Colour Temperature 3150 K
 Colour coordinates CIE 1931 (x;y) = (0.425;0.396)
 Colour deviation from BBL Duv = -0.0015

TM30-18 Colour Fidelity Index R_f 78.8
 TM30-18 Colour Gamut Index R_g 102.4
 Colour Rendering Index (Ra) CRI 81.4
 Colour Rendering Index. (red component) $R_9 = 22.5$


Colour Quality Scale CQS = 78.8
 Television Lighting Consistency Index TLCI = 56



Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	81	-9%	-4%
C2	81	-8%	8%
C3	68	-2%	17%
C4	73	7%	16%
C5	80	14%	10%
C6	80	13%	-2%
C7	74	7%	-15%
C8	85	0%	-10%
C9	85	-8%	-6%
C10	78	-11%	5%
C11	72	-6%	17%
C12	81	6%	10%
C13	85	10%	1%
C14	82	11%	-8%
C15	78	5%	-13%
C16	81	-3%	-15%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale