




Tree light pro | 36V | 10m | green wire | 3000K WW



LED tree lighting with 36V low voltage provides a tree with beautiful light, while also providing safe installation. The LEDs feature a transparent housing, allowing the lights to create a beautiful all-round appearance. Each set is easily connected, allowing you to connect up to 50 meters of tree lights to a single power supply.

Features

- 36V low voltage, ideal for safe installation in public areas
- Linkable on two sides (in and out)
- Easy in use
- Choice in length 4, 10 or 21M
- Can be cut into 150cm lengths if desired
- Max. 50 meters in one single length. Connect more lengths to one power supply? Then work with dividers to create multiple lengths of max. 50 meters each.

Article number: 025-128

CHANGED_LAST: 14-06-2023

Brand: Tronix Lighting

Type: Tree lights

ETIM Group: EG000027 - Luminaires

ETIM Classes: EC002761 - Festive lighting

SYNONYM: Bulb luminaire, Candle, Candle stick light, Chandelier, Christmas lighting, Christmas tree lighting, Curtain light, Festive lighting, Illumination cable set





Feature

Model:	Chainlight	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Number of light points:	70	Constant light output (CLO):	No
Lamp type:	LED not exchangeable	Degree of protection (IP):	IP65
With light source:	Yes	Protection class:	III
Colour:	Green	Fire resistance according to UL94:	C
Voltage type:	DC	Colour of light:	White
Nominal voltage:	36 ~ 36 V	Power factor:	0.95
Connected load:	3 W	Width:	0 mm
Battery power supply:	No	Height/depth:	0 mm
Suitable for outdoor use:	Yes	Total length:	10 m
With power bridge:	No	Diameter:	0 mm
Couplable:	Yes	Type of wiring:	Through wiring included
Type of control gear:	LED operating device voltage-controlled	Number of poles:	2
Exchangeable control gear:	No	Conductor cross section:	0.5 mm ²
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)	Connection type:	Other
Rated life time L70/B50 at 25 °C:	20000 h	commercial, christmas or lightdesign:	NA
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %		

Packaging data

Weight	560 gr
Width	98 mm
Height	80 mm
Length	200 mm
Customs code	9405310000

